

AGM

- Ideal universal battery
- Excellent starter function
- Glass fibre technology ensures low internal resistance
- Perfect upgrade for wet lead acid batteries
- 100% sealed maintenance free
- 2 year manufacturer warranty
- Threaded insert M* stud; standard supplied with easy to mount adaptive round battery terminals
- Cold cranking @ 0°F (-18°C)
- Operating temperature -4°F(-20°C) to 131°F(55°C)



AGM SERIES

Item Number	Cold Cranking Amps DIN/SAE	Dimensions in " (mm) LxWxH (w/terminals)	Capacity C20	Price
C20=battery capacity at a discharge time of 20 hours, till 1.75V per cell, dimensions include terminals				
62000900	360/570	13(330) x 6.8(173) x 8.7(220)	90 Ah	\$379.00
62001600	550/870	19.1(485) x 6.7(170) x 9.5(242)	160 Ah	\$605.00
62001300	590/940	16.1(409) x 6.9(176) x 9(228)	130 Ah	\$515.00
62002250	680/1080	20.6(522) x 9.7(240) x 8.8(224)	225 Ah	\$814.00
62002700	750/1200	20.6(522) x 10.6(268) x 8.9(226)	270 Ah	\$965.00

Slimline

- Ideal universal and starter battery
- Compressed AGM technology
- Saves up to 15% in volume and weight
- 2x 185 Ah for a 200 Ah battery footprint
- 2 year manufacturer warranty



SLIMLINE

Item Number	Cold Cranking Amps DIN/SAE	Dimensions in " (mm) LxWxH (w/terminals)	Capacity C20	Price
63001851	580/930	22(560) x 5(126) x 11(280)	200 Ah	\$771.00

Lithium Ion

- Multifunction battery of 4.3kWh
- Saves up to 70% in volume and weight
- Three times lifespan of traditional batteries
- Ultra fast charging and discharging
- Integrated Battery Management (BMS)
- Designed for systems up to 250 volts DC
- 2 year manufacturer warranty



LITHIUM ION

Item Number	Nominal Voltage	Dimensions in " (mm) LxBxH (including handles)	Capacity C20	Price
66015000	12	24.5(62.2) x 7.8(197) x 14(355)	360Ah / 5KWh	Call for pricing
66025000	24	24.5(62.2) x 7.8(197) x 14(355)	180Ah / 5KWh	Call for pricing

Images are representative of products listed and may not be actual product.