

Axial Fans

- All AC units are rated at 50/60 Hz. (50 Hz. operation will decrease CFM by 20%)
- Sleeve bearing fans must be mounted for horizontal airflow only
- Single speed
- Includes 12" wire leads unless noted (*terminal connections)



ALUMINUM HOUSING WITH TERMINALS



ALUMINUM HOUSING WITH LEADS



PLASTIC HOUSING WITH LEADS

Item Number	CFM	Volts	Watts	Amps	Dimension In " (mm)	Mounting Holes OC " (mm)	Price
-------------	-----	-------	-------	------	---------------------	--------------------------	-------

PBT Plastic Housing

Driven with brushless DC motor

4WT35	36.5	12DC	1.4	.12	3.13(79.5) x 3.13(79.5) x 1.00(25.4)	2.81(71.3)	\$59.70
6KD70	138	12DC	6.0	.833	4.69(119.1) x 4.69(119.1) 1.50(38.1)	4.13(104.9)	\$98.89
6KD74	138	24DC	9.6	.26	4.69(119.1) x 4.69(119.1) 1.50(38.1)	4.13(104.9)	\$104.91

Cast-Aluminum Housing

Driven with impedance-protected shaded pole or thermally protected PSC motor

4WT40	30	115 AC	12	0.13	3.13(79.5) x 3.13(79.5) x 1.5(38.1)	2.81(71.3)	\$90.34
4WT41	30	230 AC	16	0.08	3.13(79.5) x 3.13(79.5) x 1.5(38.1)	2.81(71.3)	\$55.55
4WT48*	70	115 AC	11	0.13	4.69(119.1) x 4.69(119.1) 1.50(38.1)	4.13(104.9)	\$84.26
4WT47*	105	115 AC	18	0.18	4.69(119.1) x 4.69(119.1) 1.50(38.1)	4.13(104.9)	\$78.57
4WT33*	105	230 AC	19	0.11	4.69(119.1) x 4.69(119.1) 1.50(38.1)	4.13(104.9)	\$84.78

Fan Accessories

- Wire guards are nickel chrome plated and can withstand 220 lb. separation force
- Plastic guards are made of UL listed 94V-0 material
- Plastic assemblies contain: fan guard, foam filter media, and retainer
- Cord sets are type SPT-1, 18/2 AWG, plugs into terminals of all standard 115 or 230 volts axial fans



GUARDS & CORDS

Item Number	Description	Dimension in " (mm)	Price
4YD95	Plastic Guard Assembly	3.13(79.5)	\$9.05
4YD86	Plastic Guard Assembly	4.71(119.6)	\$5.58
4YD96	Wire Guard (115/230V)	3.13(79.5)	\$8.80
4YD87	Wire Guard	4.71(119.6)	\$6.79
4YD79	Cord Set for Axial Fan	24L / 90° Head	\$4.86

Images are representative of products listed and may not be actual product.